



Technical Control

Inspire  
Infinite  
Creativity

## Contact Us

### Headquarter

Flat 501-502, 5/F China Shipbuilding  
Tower, 650 Cheung Sha Wan Road,  
Kowloon, Hong Kong SAR

Tel: +852 3583 2341  
Fax: +852 2407 6945  
Email: [info@techcrl.com](mailto:info@techcrl.com)

### Business Center

Dongguan Technical Control New Material Ltd.  
18/F, Blk 3, Songhu Zhigu R&D Center,  
6 Minfu Road, Liaobu Town, Dongguan,  
Guangdong Province

Tel: +86 0769-82637091/82637092  
Fax: +86 0769-82637090

### Production Site

#### China

No.7, Gantang Nine Road, Gantang  
Avenue South, Xi Lian Town, Wu Jiang  
District, Shaoguan, Guangdong  
Province, China

#### Italy

Via Lumiere 16/18 SEDRIANO (MI) ITALY

Tel: +86 0751 8130066/8130060  
Email: [info.tcsg@techcrl.com](mailto:info.tcsg@techcrl.com)



LinkedIn

WeChat

[www.techcrl.com](http://www.techcrl.com)

member of D&A Group

ADDITIVES





## High-performance Water-based Additives

Advances in the performance of waterborne coatings enable their use in a wider range of applications, high-performance water-based additives are crucial to the development of high-quality water-based coatings. The volume of additives used in coatings is very small, but they can significantly improve the performance of coatings and have become an indispensable component of coatings. In the formulation of coatings, additives can adjust the film forming properties of coatings according to market needs.

In response to the continuous sustainable development needs in different industries, Technical Control's high-performance environmentally friendly water-based additives provide customers with solutions that can improve various physical properties of coating products while ensuring product sustainability.

## Water-based Crosslinker

With the continuous improvement of environmental protection requirements in the coating industry, water-based coating products are widely used in various applications. There is increasing demand for high-performance water-based products in the market. In order to meet the needs of sustainable development of waterborne coatings, Technical Control developed a series of eco-friendly crosslinkers.

Among these, given the advantages of eco-friendly, high reactivity and stable pot life, carbodiimide crosslinker is commonly used in waterborne PU coating system. It is a new high-performance crosslinker product. Moreover, carbodiimide crosslinker has an excellent performance in the aspect of chemical resistance, anti-stain, wear-resistance and improving the toughness and adhesion of coatings. Carbodiimide crosslinker provides a new eco-friendly and safe crosslinking solution for the waterborne PU thermal set system. Our Carbolinker provides sustainable alternatives for formulators in the coating industry that ensures high performance while reducing the environmental impact.

Product Code	Ingredient	Active Content(%)	Solvent	Solvent Content (%)	Viscosity mpa.s @25°C
Isolink D70	Isocyanate	70	DMM	30	≤100
Carbolinker D30	Carbodiimide	30	WATER	70	50-300
Carbolinker D40	Carbodiimide	40	WATER	60	50-300
Carbolinker D50	Carbodiimide	50	DPM	50	200-600
Carbolinker D60	Carbodiimide	60	DPM	40	200-600
Isolink FF	Blocked Isocyanate	40	WATER	60	300-500
Isolink PCI	Blocked Isocyanate	40	DPM/WATER	5/55	300-600

## Water-based Thickener

Thickener is a rheological additive, it not only increases the viscosity of the coatings, and improve the storage stability, but also prevent the occurrence of sagging during the construction process, and can also endow the coating film with better mechanical properties. It is a very important additive for low viscosity waterborne coatings.

The water-based thickener developed by Technical Control has excellent compatibility with various water-based systems. It is characterized with excellent thickening and leveling properties, more efficient thickening effect and better viscosity stability.

Product Code	Ingredient	Hydropilic Character	Solid Content (%)	Solvent	Solvent Content(%)	Features
PT-20	Polyurethane	Nonionic	20 ±1	Water	\	High shear
PT-30	Polyurethane	Nonionic	30 ±1	Water	\	Medium to Hign shear, APEO free
PT-31	Polyurethane	Nonionic	30 ±1	Butyl Carbitol	16 ±1	Low to Medium shear, APEO free
PT-66	Polyurethane	Nonionic	40 ±1	BCS	23 ±1	Low to Medium shear, APEO free
PT-67	Polyurethane	Nonionic	40 ±1	Butyl Carbitol	23 ±1	Low to Medium shear, APEO free
PT-70	Polyurethane	Nonionic	40 ±1	Water	\	Medium shear
PT-101	Acrylic	Anionic	30 ±1	Water	\	Low to Medium shear, APEO free

## Wax Emulsion

Water-based wax emulsions are widely used for optimizing the final performance of coatings and inks by efficiently controlling the surface properties. Advancing properties like matting & gloss, hydrophobicity, soft touch, abrasion & rub resistance, scratch resistance, release, corrosion protection and anti-blocking can be achieved by adding wax emulsion.

Depending on the properties of the wax in wax emulsions, different types of wax emulsion can be used for leather topcoat finishing, paper coatings, textile coatings, film coatings etc.

Product Code	Ingredient	Appearance	Gloss	Solid Content (%)	Melting Point	pH	Application
WAX-100	Carnauba Wax	Beige Emulsion	Matt	30±1	84°C	8-10	Leather, textile, paper
WAX-101	Carnauba Wax	Dark Brown Emulsion	Glossy	30±1	84°C	8-10	Leather, textile, paper
WAX-102	Carnauba Wax	Light Grey Emulsion	Semi-glossy	30±1	84°C	8-10	Leather, textile, paper
WAX-200	Fischer-Tropsch	Milky White Emulsion	Matt	25±1	105°C	10-12	Leather
WAX-201	Fischer-Tropsch	Milky White Emulsion	Glossy	25±1	105°C	10-12	Leather
WAX-400	PE	Milky White Emulsion	Matt	40±1	120-125°C	8-10	Leather, textile, paper, film
WAX-401	PE	Light Translucent Emulsion	Glossy	35±1	137°C	6-8	Leather, textile, paper, film

